


Fire Rated O93V Expansion Submittal Sheet



STOCK NO.	LENGTH	PCS. PER BOX
O93X-V	10'	20

Description: O93X-V is a composite control joint with a single strip of intumescent tape factory applied to the back side of the control joint. O93X-V has been tested according to UL-2079 "Test for Fire Resistance of Building Joint Systems" and is used to relieve stresses of expansion and contraction of drywall interior partitions or ceilings running in a horizontal or vertical direction in both metal or wood framing on one side or both sides of the wall. O93X-V is pink in color and features a co-extruded flexible PVC center that is designed to provide protection against the stresses of expansion and contraction.

Advantages: Made from rust proof, dent resistant PVC to reduce jobsite and handling damage. Does not contain cellulose, a potential food source for mold. Intumescent tape expands when exposed to flame for increased fire protection.

Limitations: Product is designed for interior use.


Applicable Standards: Rigid PVC products meet ASTM specifications D3678-97 Class 2, D1784-03, C1047-99 and achieve a Class A rating for flame spread and smoke developed when tested under ASTM E84-10. UL-2079 Standard for Tests for Fire Resistance of Building Joint Systems.

Surface Characteristics: Trim-Tex® products are made from PVC. PVC does not support combustion and is self extinguishing when the source of flame or heat is removed.

Installation: Trim-Tex® recommends following established acceptable industry standard installation methods. Detailed installation instructions can be found at www.trim-tex.com.

Finishing: Always use a high quality paint.

Accessories: 847 Spray Adhesive and Safety Products distributed by Trim-Tex®.



Job Name _____

Contractor _____

Date _____

Approvals (Signatures or Stamps)