

Hinged Flat Access Door Panel Submittal Sheet

STOCK NO.	SIZE	STYLE
RCHG-12	12" x 12"	Slotted Radius Corner
RCHG-24	24" x 24"	Slotted Radius Corner
SQHG-12	12" x 12"	Slotted Square Corner
SQHG-24	24" x 24"	Slotted Square Corner



Description: Flat Access Door Panels are designed to blend in at locations where access is required at regular intervals.

Advantages: Created to blend in to the surroundings, Flat Access Door Panels are easy to texture or finish making them ideal for use in both new and remodeling projects. Manufactured from GFRG and 70% post-consumer recycled glass, Flat Access Door panels are resistant to moisture and mold, while providing a lightweight solution that won't shrink, sag, crack, or rust. With tapered edges for drywall installation, the surrounding frame blends seamlessly into existing walls and ceilings.

Limitations: Product is designed for interior use.

Shell Thickness	1/8" to 3/16"
Fastener Test Pull Out (wood stud)	525 lb avg.
Fastener Test Pull Out (metal stud)	215 lb avg.
Fastener Push Through Test	350 lb avg.
Fuel Contribution (ASTM E84-80)	0
Flame Spread (ASTM E84-80)	0
Smoke Index (ASTM E84-80)	0
Combustion (ASTM E84-80)	Non-combustible
Class A non-rated	—
CSI Code	CSI #08310

Job Name _____

Contractor _____

Date _____

Approvals (Signatures or Stamps)